

imagePROGRAF TX-3000 MFP T36

LARGE-FORMAT MFP OFFERING EXCEPTIONAL QUALITY, IMPRESSIVE SPEED AND INTUITIVE OPERATION.

Outstanding efficiency in tandem with unparalleled performance, from a 36-inch large-format multifunction inkjet printer built for the most exacting CAD, GIS and Poster production assignments.



- Neatly integrated chassis of the TX-3000 MFP T36 allows it to fit into crowded environments
- Accelerate productivity with advanced print head and continuous printing capability
- Simultaneous printing and scanning serves up even greater workflow efficiency
- Minimise upkeep requirements with dual-roll feeding, unique to a 36-inch MFP, and simplified roll replacement
- Economical operation made possible by LUCIA TD ink, delivering sharp detail even on cheaper uncoated paper
- Consistently accurate scanning ensured by Colortrac SingleSensor technology
- Convenient 15.6-inch colour touchscreen display and new SmartWorks user interface offers easy operation
- Flexibility to print to any network-connected TX-Series unit, thanks to universal printer driver
- Reassuring reliability provided by class-leading security specs
- Weather-resistant media printing, and board-media scanning of up to 2-mm thick

PRODUCT RANGE



imagePROGRAF TX-3000 MFP T36



imagePROGRAF TX-4000 MFP T36



imagePROGRAF TX-2000

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF TX-3000 MFP T36

SCANNER TECHNOLOGY

Scan Technology	SingleSensor
Optical Resolution (dpi)	1200
Paper path	Flat
Scan width	36" (914mm)
Min scan width	6" (15cm)
Document width	38" (965mm)
Max scan length	8m (JPEG/PDF), 15.2m (TIFF)
Weight of scanner	15Kg
Dimensions W x D x L	1109 x 324 x 153 mm
Power Supply	External power supply 100-240VAC autosensing +/-10%, 50-60Hz
Compliances	Energy Star, National: CB, Russia: EAC, EU: CE
Front/rear exit	Rear (front eject via Document Return Guide)
Document handling - Face up/down	Up
Document thickness (1)	2.0mm
Scan speed 8-bit grayscale & mono @200dpi (2)	13 inches/sec
Scan speed 24-bit colour @200dpi (2)	6.0 inches/sec
Interface USB	3.0 (backward compatible to USB2)
Scanner controls	Stop, Advance/Rewind, LED status
Branding/Colour	None / Canon black
Software (included)	SmartWorks MFP V5
OS for software	Win 8.1/10 (64 bit)
What's in the box	<ul style="list-style-type: none"> • T36 scanner • Stand assembly • 2 paper edge guides • Document return guides (3 for T36) • Calibration target • CD for SmartWorks MFP software and PDF documentation: T25/T36 Scanner User Manual and Quick Start Guide. • T36 Scanner Quick Start Guide. • USB3 cable (3 meter) • Power Supply Regional - Mains power cord(s) (2 meter)

EITHER LCD OPTION CAN BE SELECTED*

*Not available in all countries

LCD Flat Panel - PC Included (3)

LCD Type: All in One: 15.6" TFT Display, Multi-touch PC (included): System: Windows 10 Enterprise LTSB, CPU: Intel Celeron G3900 2.3GHz, RAM: 4GB DDR4, HDD: SATA 500GB, 3 x USB3 & 1 USB2 & 1 x GbE (rear), 1 x USB3 (Front)

LCD Flat Panel - PC Excluded (3)

LCD Type: 15.6" Flat Panel Touch-Screen Display

PRINTER TECHNOLOGY

Printer Type	5 Colour - 36"/914.4mm
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)
Number of Nozzles	Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each
Print Resolution	2,400 x 1,200 dpi
Nozzle Pitch	1,200 x 2 includes Non-firing nozzle detection and compensation system
Ink Capacity	Bundled Starter Ink: 330ml (MBK)/160ml (BK,C,M,Y) Sales Ink: 160ml/330ml/700ml
Ink Type	Pigment Ink: 5 colour MBK/BK/C/M/Y
OS Compatibility	Microsoft Windows: 32bit: 7.8.110, 64bit: 7.8.110, Windows Server: 2008R2, 2012/2012R2, 2016, Apple Macintosh: OS X 10.10.5 - 10.11, MacOS 10.12
Printer Languages	HP-GL/2, HP RTL, PDF, JPEG - for details check specifications
Standard Interfaces	<p>USB B Port: Type: Built in (Hi-Speed USB) Mode: Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer</p> <p>Connector Port: Series B (4 pins) USB A Port: USB Memory (Direct Print) Standard: IEEE 802.3 10base-T IEEE 802.3u 10base-TX/Auto-Negotiation IEEE 802.3ab 100base-T/Auto-Negotiation IEEE 802.3x Full Duplex</p> <p>Protocol: SNMP (Canon-MIB), HTTP, TCP/IP (IPv4/IPv6), ftp</p> <p>Wireless LAN: Standard: IEEE802.11n/IEEE802.11g/IEEE802.11b</p> <p>Security: WEP (64/128bit) WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES)</p>

MEMORY

Standard memory	128GB (Physical memory 2GB)
Expansion slot	No

HARD DISK

500GB (Encrypted)

PRINTING SPEED

CAD Drawing:	0:37 (Fast Economy Mode) 0:40 (Fast) 1:10 (Standard)
Plain Paper (AO Roll)	
Poster:	
Plain Paper (AO Roll)	0:42 (Fast Economy mode) 0:42 (Fast) 1:26 (Standard)
Heavy coated Paper (AO Roll)	1:43 (Fast) 2:37 (Standard)
PAPER HANDLING	
Media Width	Roll paper: 203.2 - 917mm Cut Sheet: 203.2 - 917mm
Media Thickness	0.07 - 0.8mm
Minimum Printable Length	203.2mm
Maximum Printable Length	Roll Paper: 18m (varies according to the OS and application) Cut Sheet: 1.6m
Maximum Media Roll Diameter	170 mm
Paper Feed Method	Roll Paper: Front loading, front output Cut Sheet: Front loading, front output (Manual feed using media locking lever)
Borderless Printing Mode (Roll Only)	[Recommend] 515mm(JIS B2), 728mm(JIS B1), 594mm(ISO A1), 841mm(ISO A0), 10", 14", 17", 24", 36" [Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 420mm(ISO A2), 8", 12", 16", 20", 30", 300mm, 500mm, 600mm, 800mm

MAXIMUM NUMBERS OF DELIVERED PRINTS

Multi-position Basket	Standard Position : 1 sheet (any image)
	Flat Position : 20 sheets (A2 landscape, any image, plain paper/coated paper)
	Basket Position : 1 sheet (any image)
	Folding Position : 100 sheets (A0/A1 portrait, CAD drawing, plain paper)
	Stacking Position : 100 sheets (A1/A2 landscape, CAD drawing, plain paper)

DIMENSIONS AND WEIGHT

Physical Dimensions and Weight	imagePROGRAF TX-3000 MFP T36 H:1356 x W:1630 x D:766mm Weight:139Kg Printer Depth dimension when the basket is closed. Dimensions and Weight include printer and basket, scanner, scanner stand and AIO Computer
Software Included	imagePROGRAF TX-Series Printer Driver, Quick Utility Toolbox, Print Plug-in for Office, Extended Survey Program and Poster Artist Lite other software is available to download from Canon's web site.

WHAT'S INCLUDED

What's in the Box?	Printer, 1 x Print Head, 1 x Maintenance Cartridge, 3" Paper Core Attachment, EU & UK Power Cable, 1 Set of Starter Ink Tanks, Set Up Guide, Safety/Standard, Software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Print head Alignment Sheet
--------------------	---

OPTIONS

Optional Items	Roll Unit: RU-32 Stacker: SS-31 2/3" Roll Holder: RH2-34
----------------	--

CONSUMABLES

User Replaceable Items	Print Head (PF-06) Ink Tanks: PFI-110(160ml), PFI-310(330ml), PFI-710(700ml) Cutter Blade (CT-07) Maintenance Cartridge (MC-30)
------------------------	--

NOTES & RECOMMENDATIONS

- Thick documents up to 2mm must be flexible and the paper return guide removed. Some media should be scanned at reduced speeds to obtain optimal image quality. Colortrac cannot guarantee to scan all media. For large media Colortrac recommend the scanner be placed on a flat surface and the operator supports the document as it enters and exits the scanner.
- The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times and quoted top speeds will depend on the host performance and are not guaranteed for all media types. True 200 x 200dpi image capture. Competitors quote scan speeds using 'Turbo', 'Normal' or 'High Speed' modes that reduce image quality whilst suggesting that scan resolution is doubled. These modes use software interpolation to create 'virtual image pixels' from a lower resolution scan thereby increasing the number of pixels in the scan direction (&/or X-direction) in an attempt to simulate higher image resolution. Colortrac SmartLF scanners are designed to scan images fast at the optimum resolution required to capture the original image detail without compromising quality.
- Please check your local supplier, some LCD options may not be available in your country.

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and * All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2018